

WIWA Air Combi Farbspritzpistole
WIWA Air Combi Spray Gun
WIWA Air Combi handspuitpistool



www.apeqwiwa.nl



WIWA Air Combi Spray Gun



WIWA Air Combi Spray Gun with Tip
Order Ref. 0632578

High performance AIR COMBI spray gun
Air assisted AIRLESS system

- Time saving design
- High transfer efficiency
- Full pattern adjustment (round to flat)
- Regular and soft spray applications
- Easy to clean & maintain
- Suitable for water based materials

Technical Data

- All parts coming into contact with materials are manufactured of stainless steel (VA 1.4305), therefore ideal for water based materials
- Max. material pressure 250 bar
- Trigger pressure adjustable from 80 - 250 bar
- Teflon needle seal
- Quick change nozzle feature
- Contoured paint tube for comfortable handling
- Separate regulations for round and flat jet
- Paint tube with material filter insert
- Swivel air & material connection
- Air consumption at 2,5 bar (36 PSI) max. 150 l/min. (5.3 cfm)
- Nozzle with additional pre-atomization nozzle available

Accessory for Air Combi Spray Gun

Tip description	Spray angle	*Spray width (mm)	Orifice		Order Ref.
			(mm)	(inch)	
218	20°	100-125	0,18	0,007	0632678
318	30°	150-175	0,18	0,007	0632679
418	40°	200-225	0,18	0,007	0633867
123	10°	100-125	0,23	0,009	0632680
223	20°	100-125	0,23	0,009	0632681
323	30°	150-175	0,23	0,009	0632682
423	40°	200-225	0,23	0,009	0632684
523	50°	250-275	0,23	0,009	0632683
623	60°	300-325	0,23	0,009	0633868
228	20°	100-125	0,28	0,011	0632685
328	30°	150-175	0,28	0,011	0632686
428	40°	200-250	0,28	0,011	0632532
528	50°	250-275	0,28	0,011	0632687
628	60°	300-325	0,28	0,011	0632476

Filter Insert M 50 -white- Order Ref. 0632866
 Filter Insert M 100 -yellow- Order Ref. 0632867
 Filter Insert M 150 -red- Order Ref. 0632868

Tip description	Spray angle	*Spray width (mm)	Orifice		Order Ref.
			(mm)	(inch)	
233	20°	100-125	0,33	0,013	0632688
333	30°	150-175	0,33	0,013	0632472
433	40°	200-225	0,33	0,013	0632689
533	50°	250-275	0,33	0,013	0632690
633	60°	300-325	0,33	0,013	0632468
238	20°	100-150	0,38	0,015	0632691
338	30°	150-200	0,38	0,015	0632692
438	40°	200-250	0,38	0,015	0632693
538	50°	250-300	0,38	0,015	0632694
638	60°	300-350	0,38	0,015	0632492
446	40°	200-250	0,46	0,018	0633506
453	40°	200-250	0,53	0,021	0638037
653	60°	300-350	0,53	0,021	0638038

*at a distance of 30 cm approx. from object.

Special orifices and width are available if required:
 – Spray angle 10° - 140°
 – Orifice 0,13 - 1,55 mm

WIWA

Wilhelm Wagner GmbH & Co. KG
 Gewerbestraße 1-3 • 35633 Lahnau, Germany
 P.O.B. 29 • 35631 Lahnau, Germany
 E-mail: info@wiwa.de • Internet: www.wiwa.de
 Telephone: +49 (0)64 41-6 09-0
 Telefax: +49 (0)64 41-6 09-50/58

Technical changes reserved.

No. 0518625 (e) · 02.01

© Copyright 2001 WIWA Wilhelm Wagner GmbH & Co. KG

Your local distributor is: